

OEM Item Request List / 客製 OEM 規格表

1. Bearing No. 型號/規格	2. Outer/Inner Rings 內外套圈	3. Cage 保持器	4. Balls 球珠	Application 適用場合
6000	SUS440	Nylon	SUS440	LCD/FTP/LED Cleaning
6900	SUS304	PP	SUS304	Wafer Cleaning
6800	UPE	UPE	Glass	Liquid Crystal Cleaning
6200	PP	PEEK	PP	Etching Process
6300	POM	PVDF	PEEK	High Temperature Process
7000	PEEK	PTFE	PVDF	Semiconductor CMP Process
7900	PVDF	SUS440	ZrO ₂	Food Equipment
7200	PTFE	Non Cage	Si ₃ N ₄	Metal or Mining Equipment
51000	ZrO ₂ /SiC			Any Chemical Base Environment
Customize				



CAM 軸承公差 Tolerance of special bearings



(inner and outer)

材料 material	外徑 D(mm) Outside diameter	內徑 d(mm) Bore diameter	高度 W(mm) Width
PEEK	0/ - 0.03	+ 0.03/0	0/ - 0.1
POM	0/ - 0.03	+ 0.03/0	0/ - 0.1
PP	0/ - 0.03	+ 0.03/0	0/ - 0.1
PVDF	0/ - 0.03	+ 0.03/0	0/ - 0.1
PE	0/ - 0.03	+ 0.03/0	0/ - 0.1
UPE	0/ - 0.03	+ 0.03/0	0/ - 0.1
PTFE	0/ - 0.03	+ 0.03/0	0/ - 0.1
Ceramic	0/ - 0.01	0/ - 0.01	0/ - 0.01

備註:以上公差精度標示為尺寸 30mm 以下之軸承,隨著尺寸增大公差尺寸亦將加大,請依需求與本公司再次確認!